

STRAIGHT GRINDER SYSTEM

DESCRIPTION

The Straight Grinder System is fully ATEX certified for use in Zones 1 and 2 areas without the need for a Hot Work Permit. It can perform a wide range of grinding tasks using the varied files supplied as part of the system. They files are designed to provide a range of practical solutions when working with steel and with non-ferrous materials, specifically aluminium and also passive fire protection materials such as chartek and fendolite materials.

KEY FEATURES

COLD WORK PERMIT

EASE OF USE

SAFETY TRIGGER

UNIVERSAL AIR CONNECTION



COMPATIBLE EQUIPMENT

						
PRODUCT CODE	APT-101-CL1	APT-101-CL2	APT-101-CL3	APT-101-TR1	APT-101-TR2	APT-101-TR3
WORKABLE MATERIALS	STEEL	STEEL	STEEL	STEEL	STEEL	ALUMINIUM, CHARTEK AND FENDOLITE

TECHNICAL SPECIFICATION

CERTIFICATION & MARKING	ATEX Cert: DNV 12 ATEX 14513X Ex II 2G c IIA T160°C II 2D c T160°C I M2 c T160°C
OPERATING TEMPERATURE	-20°C to +40°C
MAXIMUM AIR PRESSURE (BAR)	6.3
AIR HOSE DIAMETER	3/8"
MOTOR SPEED (RPM)	3000
MAXIMUM CFM UNDER LOAD	38.2
WEIGHT (KG)	2.2
VIBRATION VALUE (M/S ²)	2.7
SOUND PRESSURE LEVEL (dBA)	74

© 2019 Safehouse Habitats Scotland Ltd. All rights reserved. Copyright of this publication belongs to Safehouse Habitats and this document must not be copied or reproduced in whole or in part or in any manner or form or otherwise without the prior consent of Safehouse Habitats.